

# Cal 25 Standard Standing, Running Rigging, Spinnaker & Reefing Gear Specification

(As defined by Jensen Marine)

# Pcs Req'd	Description	Material Specification	Length	Terminal Hardware
<b>Standing Rigging</b>				
1	Headstay	5/32" 1x19 s/s	30' 6 1/2"	Marine Eye & 5/16 Threaded Shank
1	Backstay	5/32" 1x19 s/s	26' 2 5/8"	Marine Eye & 5/16 Threaded Shank
2	Backstay Bridles	1/8" 1x19 s/s	6' 11 1/4"	Marine Fork Each End
1	Boomlift	1/8" 7x19 s/s	1' 6"	Nicro Press Loop & Snap Hook
2	Uppers	5/32" 1x19 s/s	29' 0"	Marine Fork & 5/16 Threaded Shank
2	Lowes	3/16" 1/19 s/s	14' 5"	Marine Fork & 3/8 Threaded Shank
2	Life Lines	1/8" 1x19 s/s	18' 4"	Marine Fork & 1/4 Threaded Shank

All dimensions are center eye to eye or end of threaded shank.  
On insulated backstays, keep insulators as far apart as possible.

<b>Running Rigging</b>				
1	Main Halyard	1/8" 1x19 s/s	28'	Wire Rope
1	Jib Halyard	1/8" 1x19 s/s	31'	Wire Rope
2	Halyard Tails	5/16"	31'	Dacron Yacht Braid
1	Mainsheet	5/16"	80'	Dacron Yacht Braid
2	Jibsheet	3/8"	30'	Dacron Yacht Braid
1	Outhaul	1/8"	4'	Dacron Yacht Braid
1	Downhaul	1/4"	4'	Dacron Yacht Braid

<b>Spinnaker Gear</b>				
1	Spinnaker Halyard	5/16"	70'	Dacron Yacht Braid
2	Spinnaker Sheets	5/16"	38'	Dacron Yacht Braid
1	Topping Lift	5/16"	40'	Dacron Yacht Braid
1	Foreguy	1/4"	35'	Dacron Yacht Braid

<b>Reefing Gear</b>				
1	Clew Pennant	5/16"	24'	Dacron Yacht Braid
1	Tack Pennant	1/4"	15'	Dacron Yacht Braid

This is an electronic copy of information that was proeviously only available in hard copy.  
The spreadsheet reflects the data as defined in the original document. Tiles have been added and the format change slightly for ease of use.  
Brian Shenstone 12-3/2006